# IP Video Surveillance VN2004–Q1 **Network Video Recorder**







### **Overview**

VIDEOTEKNIKA 2000 Series is a reliable range of Network Video Recorders with Full HD 1080p local display capability and recording benchmark of up to 8 Megapixel. The VN2004–Q1 ensures unleveled video recording quality in multiple applications on an open platform in live and also in playback. The VN2004–Q1 has a standard availability of 1 Hard Disks bays allowing recording capacity of up to 6TB. Backup facility is available via the network ports through the VVMS and allows for local backups via USB.

#### Supported Cameras

The VN2004–Q1 supports all Videoteknika IP Cameras and is fully compatible with our Videoteknika's VVMS Software. The VN2004–Q1 functions on an open platform policy allowing for various 3rd party IP camera integration. Within the Videoteknika range various video encoders and video decoders are available to further more expand the flexibility for the system integrator and ensure total system synchronization. Each channel on–board the NVR allows for dual streaming with the mainstream supporting up to 8MP of record–ing resolution.

#### Storage Features

The VN2OO4–Q1 allows for individual channel recording allocation ensuring the right data capacity is assigned through the relative camera depending on its streaming resolution. Instant playback is also possible via the Videoteknika reverse instant playback capability which is unique to Videoteknika NVRs. Digital zooming while live or playback is standard with any high resolution recording camera.

#### Supported Software

The NVR is supported by the Videoteknika VVMS-Xpert<sup>™</sup> VMS. The VVMS-Xpert<sup>™</sup> VMS is a modular Video Management Software dedicated for Videoteknika IP cameras expandable up to 1024 Channels per server. A 64 Ch version VVMS-Advanced<sup>™</sup> is supplied as a free bundled software with all Videoteknika IP Cameras. VVMS-Mobile<sup>™</sup> is also available on Iphone and Android applications. Videoteknika IP cameras are supported by various leading software development VMS partners.

### **Main Features**

- Recording Quality up to 8MP
- 2–Way Audio
- Up to 6 Terabytes of Hard Disk space
- Self Adaptive 10m/100m/1000m network interface
- H.265 video compression
- Dual Simultaneous Streaming
- Simultaneous HDMI & VGA outputs
- HDMI & VGA (Full HD 1080p) output
- Local Data Export via USB
- Network backup export via Videoteknika VVMS software
- Multiple level users Administrator / User 1 / User 2 (programmable)
- Privacy Masking
- Videoteknika VVMS-Advanced<sup>™</sup> VMS software included
- Videoteknika VVMS-Mobile<sup>™</sup> supported on App Store



# IP Video Surveillance VN2004–Q1 **Network Video Recorder**


## **Specifications**

NVR Model	VN2004-Q1	
Features		
IP Video Input	4–Channels	
Two–way Audio	1–ch, BNC (2.0 Vp–p, 1kΩ)	
<b>Recording Resolution</b>	8MP / 5MP / 3MP / 1080P / UXGA / 720P /	
	VGA/4CIF/DCIF/2CIF/CIF/QCIF	
HDMI Output	1–ch, resolution: 1920 x 1080P / 60Hz,	
	1920 x 1080P / 50Hz, 1600 x 1200 / 60Hz,	
	1280 x 1024 / 60Hz, 1280 x 720 / 60Hz,	
	1024 x 768 / 60Hz	
VGA Output 1-ch, resolution: 1920 x 1080P / 60		
	1600 x 1200 / 60Hz, 1280 x 1024 / 60Hz,	
	1280 x 720 / 60Hz, 1024 x 768 / 60Hz	
Audio Output 1-ch, BNC (Linear, 600Ω)		
Playback Resolution 8MP / 5MP / 3MP / 1080P / UXGA / 720P		
	VGA/4CIF/DCIF/2CIF/CIF/QCIF	
Synchronous Playback 16-Channels		
SATA	1 SATA interfaces	
Capacity Each interface supports up to 6TB capacity for recording		

NVR Model	VN2004-Q1		
Features (Continue)			
Network Interface	1 RJ-45 10 / 100 / 1000 Mbps self-adaptive		
	Ethernet interface		
Serial Interface	1 RS-232, 1 RS-485 & 1 RS-485 keyboard		
USB Interface	2, USB 2.0		
Environmental			
2	-10°C ~+55°C		
Working Temperature			
Working Humidity	10 % ~ 90 %		
Electrical			
Power Supply	12 VDC		
Power Consumption	≤ 10W		
Physical			
Dimensions (mm)	315 X 240 X 48 mm		
Chassis	1U chassis		
Weight	≤ 1 Kg (2.2 lb)		
Regulatory Certifications	FCC, CE, C-TICK, UL		

**XX** VIDEOTEKNIKA

# **Technical Diagram**



Real Panel	Real Panel (Continue)
1. Audio In	7. Power Switch
2. Audio Out	8. LAN Network Interface
3. VGA Interface	
4. HDMI Interface	
5. USB Interface	
6. DC12V	



# IP Video Surveillance VN2004–Q1 **Network Video Recorder**



## **Ordering Information**

NVR Model	Network Video Recorder Details	
VN2004-Q1	4–Ch, D1 to 8MP Recording Quality (Depending on Storage & Bandwith Requirements), Up to Max. 5 TB of HDD space,	
H.265, Dual Streaming, Simultaneous HDMI & VGA outputs, Local Data Export, Network Backup		

## **Recommended Associated Products**







VVMS-Advanced <sup>™</sup>	VVMS-Xpert <sup>™</sup>	VVMS-Mobile <sup>™</sup>
Video Management Software	Video Management Software	Mobile Application
64 Channel	1024 Channel	
Mobile Application	Mobile Application	

### **Affiliations:**





### **Partners**:



















VIDEOTEKNIKA SRL – SANSEPOLCRO (AR) VIA DEL PETRETO 4 CAP 52037Videoteknika SRL (Perugia) Registered in Chambers of Commerce, Arezzo, Italy. Registration No. 21761Website: www.videoteknika.comEmail : sales@videoteknika.com